





EMS REDLINE - Drive Recorder (DR4000) Component Price List

Model No.	Description	Pricing
4 Channel Mobile "BLACK BOX" DRIVE RECORDER		EMS REDLINE Price (US \$)
<p>OP DR4000 Smart Black Box Recorder</p> 	<p>4 Ch. Drive Recorder Black Box (5V Camera System) Modes: Continious / Event / Emergency Button Recording Memory: 4GB SDHC (supports 32GB SDHC) Compression: MPEG4 & MJPEG External GPS, Car Speed, & Google Earth Support Internal 3 Axis G Sensor, RTC, Super Capacitor Locking Steel Housing w/Key 4 Video In / 1 Audio In / 3 Alarm In (Door, Taxi Meter, Etc.) Advanced Daya Analysis & Reporting Software Record Resolution: NTSC 720x480, 720x240, 360x240 Record Speed: NTSC: 60fps(720x480), 120fps(720x240) Very small & compact size : 70 X 99 X 21 mm, 100g</p> <p>Includes: DR4000, 4GB HDD, Steel Lockbox, GPS, Panic Remote, Power/Input Cables</p>	<p>\$495.00</p>
DR4000 CAMERAS		EMS REDLINE Price (US \$)
<p>OP 100-IR</p>  <p><i>*Passenger Cam (Interior)</i></p>	<p>DC 5V, CCD IR camera for DR4000 1/3" Sony Super HAD CCD II Angle of View: 145° Effective Pixel: 510(H) X 492(V) (NTSC), 500(H) X 582(V) (PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: IR LED On 0 lux Operating Temperature: -20°C ~ 60°C Input Voltage: 5V, Power consumption: Max. 320mA(LED ON) 43mm x 38mm x 35mm, 70g, Wire : L=5000±10mm</p>	<p>\$165.00</p>
<p>OP 100</p>  <p><i>*Forward Facing Through Window(Interior)</i></p>	<p>DC 5V, CCD camera for DR4000 1/3" Sony Super HAD CCD II Angle of View: 90° Effective Pixel: 510(H) X 492(V) (NTSC), 500(H) X 582(V) (PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: 0.1 lux Operating Temperature: -20°C ~ 60°C Input Voltage: 5V, Power consumption: Max 200mA 43mm x 38mm x 35mm, 70g, Wire : L=5000±10mm</p>	<p>\$165.00</p>
<p>OP 120M</p>  <p><i>*Back Up Camera (Exterior)</i></p>	<p>CMOS Rear View Camera, Waterproof (IP 68) 1/4" Hi Resolution CMOS Angle of View: 162° Min. Illumination: 1 lux Operating Temperature: -30°C ~ 85°C Input Voltage: DC 12V Power consumption: Max. 35mA 28.00 x 29.00 x26.00 mm, 113g Include 8m extension cable</p>	<p>\$175.00</p>

* Full specifications and product manuals on request

* COPYRIGHTS© 2011 Optimo Electronics, Inc.. All RIGHTS RESERVED